

Features :


- Green design, No-load power consumption < 0.3W
- Universal AC input / Full range
- Protections: Short circuit / Over load / Over voltage
Brown-out (Low AC Input voltage)
- Medical safety approved
- Fully isolated plastic case
- Isolation class II
- All using 105°C long life electrolytic capacitors
- High operation temperature up to 70°C
- 100% full load burn-in test
- Withstand 2G vibration test
- Cooling by free air convection
- 3 years warranty




MODEL		ME-05-05	ME-05-12	ME-05-15	ME-05-24	
OUTPUT	DC Voltage Range	5V	12V	15V	24V	
	Rated Current	1A	0.42A	0.33A	0.21A	
	Current Range	0 ~ 1A	0 ~ 0.42A	0 ~ 0.33A	0 ~ 0.21A	
	Rated Power	5W	5.04W	4.95W	5.04W	
	Ripple & Noise (max.)	100 mv	150 mv	150 mv	240 mv	
	Voltage Tolerance	+5 / -3%				
	Line Regulation	Note.8	±0.5%			
	Load Regulation	Note.8	±1.0%	±0.5%	±0.5%	±0.5%
	Setup, Rise Time	100ms, 25ms/230VAC 100ms, 25ms/115VAC at full load				
	Hold Up Time	100ms / 230VAC 25ms / 115VAC at full load				
INPUT	Voltage Range	85V ~ 264VAC 125 ~ 373VDC				
	Frequency Range	47Hz ~ 63Hz				
	Efficiency (Typ.) at 230Vac	71%	75%	75%	77%	
	AC Current (Typ.)	0.13 A / 115VAC 0.08A / 230VAC				
	Inrush Current (Typ.)	Cold Start 25A / 115VAC 45A / 230VAC				
Protection	Over Load	Above 110% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed				
	Over Voltage	115% ~ 145% rated output voltage Protection type : latch-off mode				
Environment	Working Temp.	-20°C ~ 70°C (Refer to output load de-rating curve)				
	Working Humidity	20 ~ 90% RH non-condensing				
	Storage Temp., Humidity	-40 ~ +85°C, 10 ~ 95% R.H				
	Temp.Coefficient	±0.03%/°C (0 ~ 50°C)				
	Vibration	10 ~ 500Hz, 2G 10min/1cycle, period for 60 min each along X,Y,Z axes				
Safety & EMC	Safety Standards	UL60601-1 / TUV EN60601-1 / IEC60601-1 Approved				
	Withstand Voltage	I/P - O/P: 4KVAC				
	Isolation Resistance	I/P - O/P: 100M Ohms / 500VDC				
	EMI Conduction & Radiation	EN55011: 2007+A2: 2007 Class B				
	Harmonic Current	EN61000-3-2: 2006 Class A, EN61000-3-3: 1995+A1: 2001+A2: 2005				
	EMS Immunity	EN60601-1-2: 2001+A1: 2006, IEC61000-4-2,3,4,5,6,8, 11 light industry level, criteria A				
Others	MTBF	217.4K HRS Compliance: MIL-HDBK-217F				
	Dimension (L*W*H)(mm)	62.85x50x19.7				
	Packing	0.033kg ; 144Pcs/7.05kg				
Note	<p>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.</p> <p>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47 uf parallel capacitor.</p> <p>3. Tolerance: includes set up tolerance, line regulation and load regulation.</p> <p>4. Line regulation is measured from low line to high line at rated load.</p> <p>5. Load regulation is measured from 10% to 100% rated load.</p> <p>6. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.</p> <p>7. Length of set up time is measured at cold first start. Turning ON/OFF the power supply very quickly may lead to increase of the set up time</p> <p>8. The line regulation and load regulation is calculated based on output voltage.</p>					

Unit : mm

Mechanical Specification



Block Diagram



De-rating Curve

