

12 Watt Medical Series

Wall Mount Type USA / Europe / UK

ATM012 - W <u>X X X</u>

O/P Voltage

►	U	ż	US	Plug
	Е	ż	EU	Plug
	_			Plua

Output

•			
Load Regulation	±5% (Typical)		
Ripple	1 ~ 2% Vp-p Max. for Output Voltage		
Кірріе	@ Full Load		
Transient Response	0.5mS for 50% Load Change Typical		
Hold-up Time	10mS @ Full Load		
Protection	Short Circuit Protection / Over Voltage		
FIDIECTION	Protection / Over Current Protection		
DC Cord	22AWG / 20AWG / 18AWG		
Ferrite Core	Yes		

Safety Approvals

For USA - UL / cUL / FCC For Europe & UK - CE

Electrical			
Topology	Switching Flyback		
Dielectric Withstand	4000VAC Primary - Secondary		
Touch Current	< 100µA		
Efficiency	Energy Star Level V, ErP Stage 2, NRCan & GEMS Certified		
EMI Conduction & Radiation	Compliance to EN55011 Class B		
Harmonic Current	Compliance to EN61000-3-2, 3		
EMS Immunity	Compliance to IEC60601-1-2		
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332		

Environmental			
Operating Temperature	0 to + 40°C		
Storage Temperature	-20 to + 80°C		
Deletive Uveridity	Operating : 20 to 80% RH		
Relative Humidity	Storage : 10 to 90% RH		
Cooling	Natural Convection Cooling		

Green Mode

Meet CEC, Energy Star Level VI, ErP Stage 2, NRCan & GEMS NO Load Power Consumption Less 0.1W

Features :

- ANSI/AAMI/IEC/EN ES60601-1:2005 (60601 3rd edition)
- IEC 60950 approval
- Means of Protection: 2 X MOPP
- Touch Current : < 100µA
- 100-240VAC Universal Input
- Single Output to 12W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 2 Years Warranty

Model	O/P Voltage	O/P Current	Watt
ATM012-W050□	5.0V	2.00A	10.00W
ATM012-W060□	5.9V	1.70A	10.00W
ATM012-W075□	7.5V	1.33A	10.00W
ATM012-W090□	9.0V	1.12A	10.00W
ATM012-W120□	12.0V	1.00A	12.00W
ATM012-W150□	15.0V	0.80A	12.00W
ATM012-W180□	18.0V	0.67A	12.00W
ATM012-W240□	24.0V	0.50A	12.00W

Input

• • • • • • • • • • • • • • • • • • •		
Voltage	100-240VAC	
Line Frequency	50-60Hz	
Current	0.31A-0.17A	
Protection	Internal Primary Current Fuse , Inrush Limiting	
	U for US Plug	
Configuration	E for EU Plug	
	B for UK Plug	