

Features :

- 0.98 typical of power factor
- High reliability and low ripple noise
- Built-in remote sense function
- Built-in remote ON/OFF control
- Built-in power good signal output
- Programmable output voltage
- Forced current sharing at parallel operation
- Output short circuit / over voltage / overload / over temperature protections
- CB, CE, UL, TUV approved



MODEL		1K5U-P012	1K5U-P015	1K5U-P018	1K5U-P024	1K5U-P030	1K5U-P036	1K5U-P048	1K5U-P060	
Output	DC Voltage	12V	15V	18V	24V	30V	36V	48V	60V	
	Rated Current	125A	100A	83A	62A	50A	41A	31A	25A	
	Rated Power	1500W	1500W	1494W	1488W	1500W	1476W	1488W	1500W	
	Ripple & Noise (max.)	150mVp-p	150mVp-p	180mVp-p	240mVp-p	300mVp-p	360mVp-p	480mVp-p	600mVp-p	
	Voltage Adj. Range	+3% ~ -12% typical adjustment by potentiometer; 20% ~ 100% adjustment by 1 ~ 5VDC external control								
	Line & Load Regulation	Less than 1%								
	Setup, Rise, Hold Time	800ms, 400ms, 12ms at full load								
Input	Voltage Range	180 ~ 260VAC / 260 ~ 370VAC								
	frequency Range	47 ~ 63Hz								
	Power Factor (Typ.)	0.98 / 230VAC								
	Efficiency (Typ.)	84%	85%	85%	88%	88%	88%	89%	90%	
	AC Current (Typ.)	9.0A / 230VAC								
	Inrush current (Typ.)	120A / 230VAC								
Protection	Leakage Current (max.)	< 7.0mA / 240VAC								
	Over Load	105 ~ 115% rated output power (Current limiting, delay shut down output voltage, re-power on to recover)								
	Over Voltage	110 ~ 135% follow to output set up point(shut down output voltage, re-power on to recover)								
Environment	Over Temperature	>100°C / measure by heat sink, near transformer (shut down output voltage, recovers automatically after temperature goes down)								
	Working Temp. & Humidity	0 ~ +50°C; @100% Load, +65°C @50% Load; 20% ~ 90% RH non-condensing								
	Storage Temp.& Humidity	-20 ~ +85°C, 10 ~ 95%RH								
Safety & EMC	Temp.Coefficint	±0.04% / °C (0 ~ 50°C)								
	Safety Standards	UL1950, TUV EN60950-1 Approved								
	Withstand Voltage	I/P - O/P : 3KVAC; I/P - FG : 1.5KVAC; O/P - FG : 0.5KVAC								
	Isolation Resistance	I/P - O/P, I/P - FG, O/P - FG : 100M Ohms / 500VDC								
	EMI Conduction & Radiation	Compliance to EN55022 Class A								
	Harmonic Current	Compliance to EN61000-3-2,3								
Others	EMS Immunity	Compliance to EN55024								
	Power Good Signal	Open collector N MOSFET								
	Special Function	DC voltage adj., Remote sensing, Remote control, Parallel operation								
	Cooling	Power rating and temperature controlled cooling fan								
	Dimension (L*W*H)(mm)	290x205x64mm (LxWxH)								
Packing	3.7kg ; 4sets / 18kgs / Carton									